

BearCreeks BCBA06 3+1 Bite Alarm

Bite alarm units

- 8 tones settings
- 8 volume settings
- 5 sensitivity settings
- 15 sec latching LED
- 8 magnet rollers
- Running LED (all are white)
- Push button LED dimmer
- Black satin smooth finish
- Colorful light rollers
- 220-280 meters
- Operates with the 1.5V * 2 batteries
- 2.5mm jack socket
- Memory function in bite alarm
- Removable storm ears
- Low battery function



Technical Specification

Transmitter:

- Power Voltage: 1.5 V * 2
- Standby Current: 35uA
- Working current: 70mA
- Shut down current: 14UmA
- Turn on night light standby current: 1.2 m A
- Working Power: 12dB
- Frequency: 433MHz
- Coverge range:220-280m
- Working Temperture: 10-70 *C

Receiver:

- Power voltage: 1.5V *3
- Standby Current: 2.5mA
- Working current: 50mA
- Shut Down Current: 40mA
- Receiving Sensitivity:105dB
- Frequency: 433MHz
- Coverage Range: 220-280m
- Working Temperature: 10-70*C

Alarms User Instructions

Inserting battery

Slide down battery cover ----- insert 1.5V * battery. To complete the procedure, gently push back the battery cover.

Power on/off switch

Power ON- press the T/Power button for 3 second stop turn on. Power off press the T/power button for 3 seconds to shut down.

Volume adjustment

Press the volume control "V"to step through the 8 volume settings, ranging from low to high and silent mode.

Tone adjustment

Press the tone adjustment button "T" to step through the 8 settings.

On/Off Light switch

Press the light control "S" to set ON/OFF night light for 3 seconds (on/off).

Sensitivity adjustment

Press the sensitivity adjustment button 'S' to step the 5 sensitivity settings, running to minimum to maximum mode.1 beep equals maximum sensitivity to 5 beeps minimum sensitvity.

Run indication/Low battery indication

Low voltage detection, when the voltage is lower than 2.5V, the running light will flash for 5 seconds.

Receiver units

- 8 tones settings
- 8 volume settings
- 5 colors clear LED choices
- Vibration mode/Silent mode
- 5 LED dimmer
- 220-280 meters
- Memory function to receiver
- Lear and erase code
- Low battery function
- Operate with 1.5V*3batteries



Receiver User Instructions

Inserting battery

Slide down battery cover ----- insert 1.5V * battery. To complete the procedure, gently push back the battery cover.

Power on/off switch

Power ON- press the T/Power button for 3 second stop turn on. Power off press the T/power button for 3 seconds to shut down.

Volume adjustment

Press the volume control "V"to step through the 8 volume settings, ranging from low to high and silent mode.

Vibration adjustment

Press the vibration button to choose vibration mode on or off.

Low battery indication

When the voltage is lower than 3.2V, the bottom purple light will flash for 5 seconds.

Learning method

Press the `M` button for 3 seconds to enter the code mode, then click the `M` button to jump the light to select the code position. After the position is selected. Turn the transmitter wheel, the receiver light starts flashing when it receives signal rings, that is to complete the code. When you need to learn other bite alarm, repeat the above operation.

Erase method

Long press the `M` button for 6 seconds to clear the code mode, all the lights lit, and the sound dripped twice, erasing successfully and all code of bite alarm which had been stored are erased.

You can find more articles for a new genre of fishing on our website: <https://www.bearcreeks.com/>